



## (HG) High-Gloss PAVER SEAL



1 US gal. • 5 US gal. • 55 US gal.

### SRW (HG) High-Gloss PAVER SEAL

**SRW (HG) High Gloss Paver Seal™** sealer and sand stabilizer provides a clear, high-gloss, protective barrier that extends the life of your pavers and concrete surface. This barrier protects the pavers against elements which can stain and deteriorate their appearance, such a rust, oil, dirt, pool chemicals, salt and every day weathering. In one application, HG also stabilizes joint sand, adding protection against sand washout, weed growth and ant infestations.

- “Wet-look”/High-gloss finish
- Breathable
- Enhances, restores & protects
- Protects joint sand from washout, weeds and ants
- Interior/Exterior
- Water-based

### DIRECTIONS

1. Thoroughly clean surface of joint sand, dust or loose material prior to application. Use SRW (EF) Paver Wash and Efflorescence Cleaner for general cleaning, paver prep and removal of efflorescence. If necessary, use SRW (CD) Cleaner/Degreaser for removal of stains and SRW (RE) Rust Eliminator for removal of rust.
2. Surface must be completely dry prior to sealer application. Recommended application temperatures are 50°F (10°C) to 80°F (27°C). Do not apply if inclement weather is forecasted within 24 hours.
3. **STIR THOROUGHLY PRIOR TO USE.** Product may settle. Do not dilute before applying. Can be applied with a sprayer or roller. For best results, apply with a clean, low pressure sprayer that is approved for solvent usage. Start at the highest elevation of the pavement. Immediately follow up by back rolling the sealer using a SRW Slit Foam Roller. This process will even out the application and prevent an uneven finish. Do not allow sealer to pool on the pavers or joints.
4. Allow sealed area to dry (24-hours). Protect from water and rain until dry. Dry-tack free: 25 minutes; Foot traffic: 24 hours; Vehicle traffic: 72 hours (Note: All calculations based upon 68-77° F (20-25° C). High humidity will increase drying time.

**Cleanup** • Clean with soap and warm water.

**Coverage:** 100-150 sq. ft. per gallon, exterior pavement coverage (based on an 1/8” joint spacing). Quantity may vary depending on surface and application.

### USER TIPS

- Most pavement manufacture’s recommend waiting 90 days to seal new pavement.
- For a deeper sheen, apply a 2nd thin coat, 4 hours after 1st coat. Do not over apply.
- For added slip-resistance, use **SRW (SR) Slip Resistant Paver Grip**.
- Do not apply to structures under hydrostatic pressure
- Care should be taken for vertical surface application where runs may alter the finish.
- Do not overwork the material (stringiness will start to appear).
- Not recommended for use on clay pavers, granite, bluestone and slate.

## PACKAGING

| PART NUMBER               | SIZE         | # PER CARTON OR PALLET      | LBS                      |
|---------------------------|--------------|-----------------------------|--------------------------|
| SSPSPRO GAL / SSPSPRO CTN | 1 US Gallon  | 4/carton; 36 cartons/pallet | 35/carton<br>1350/pallet |
| SSPSPRO 5GAL              | 5 US Gallon  | 36/pallet                   | 47/pail<br>1692/pallet   |
| SSPSPRO 55GAL             | 55 US Gallon | NA                          | 485                      |

## WARNINGS

**KEEP PRODUCT FROM FREEZING.  
KEEP OUT OF REACH OF CHILDREN.**

### PHYSICAL PROPERTIES

Wet appearance: Milky White  
 Dry appearance: Clear  
 Solids: 30% minimum

### HEALTH AND SAFETY

- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Use of respirators is advised when using in confined areas.

**Caution:** Protect buildings, landscaping and vehicles from overspray or spray drift.

**Storage:** Keep from freezing. Store container in a cool area, away from heat and open flame, with cap or lid firmly in place.

**Warning:** Do not inhale spray mist. Irritating to skin and eyes. In case of eye contact, flush with water for at least 15 minutes. Wash exposed skin with warm, soapy water. If irritation persists, see a physician. If ingested, do NOT induce vomiting. Dilute by drinking water. Seek medical attention. Always wear a mask and protective eyewear and clothing. **Keep out of reach of children.**

### Important Notice:

Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.