



## SRW (SR) Paver Grip

SRW (SR) Paver Grip™ is a slip-resistant polypropylene aggregate that can be added to SRW HG Paver Seal and LG Paver Seal to create a textured surface improving slip resistance. The particles are light-weight and clear, keeping them in suspension longer than other aggregates. Paver Grip can be used in clear coatings without discoloration.

- Improves slip-resistance on pavers and concrete surfaces
- Lightweight, clear appearance
- Will not discolor

## DIRECTIONS

1. Add the contents of this container to 5-gallons of SRW HG Paver Seal and/or LG Paver Seal. Mix until aggregate is distributed uniformly throughout entire liquid. Periodically stir during use to assure uniform distribution. (Measurements are below for mixing quantities less than 5 gallons.)
2. Follow surface preparation and application instructions for the coating being applied. When using Paver Grip, SRW recommends rolling product on with the second application of sealer. This will minimize sand being pulled from the joints and adhering to the surface of work area.
3. Do not re-roll wet areas. Paver Grip will not protrude through a film with a dry film thickness greater than the diameter of the texture such as a high-build Epoxy. In these situations a coarser aggregate will be required.

## USER TIPS

### Measurements:

- 5 gallons Paver Seal™ - use 1 lb. of Paver Grip  
 1 gallon Paver Seal™ - use 1 cup of Paver Grip

## PACKAGING

PART NUMBER	SIZE	# PER CARTON OR PALLET	LBS
SSSR PG	1 LB	4/ctn	-

## WARNINGS

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache or nausea. Causes eye irritation. Causes skin irritation. Causes nose and throat irritation. May cause allergic skin reaction. Harmful if swallowed. Use only with adequate ventilation. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection. (NIOSH/MSHA approved). Any person using a respirator must be properly trained in respirator use. Close container after each use. Avoid contact with eyes and skin. Dispose of empty containers in accordance to all applicable regulations.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately thoroughly with soap and water. If swallowed, do not induce vomiting. Give conscious victim 1 to 2 glasses of water and get medical attention immediately.